


## AEM350



### What's in the Box:

- AEM350
- Remote Control
- AC Adapter
- Webcam cover
- USB Cable (2 m)
- User Guide
- AAA Battery x2
- Screws x4
- Drywall Anchors x4
- L Bracket
- Thumb screws



### Targus® All-in-One 4K Video Conference System

Camera	
Lens Construction	6 element - 4G2P
Lens Aperture	f/2.2
Lens Field of View (FoV) - Horizontal / Vertical / Diagonal	H: 120 degrees / V: 76 degrees / D: 128 degrees
Lens unit Pan & Tilt - Horizontal / Vertical	Manual - H: 8 degrees (total 16 degrees) / V: 5 degrees (total 10 degrees)
Total Room Coverage (field of view + pan and tilt)	H: 136 degrees / V: 86 degrees
Auto Focus	No - Fixed Focus
Auto Focus method	N/A
Lens Focal length	N/A
Sensor Type	Sony Low-illumination CMOS
Sensor Size	1/2.8-type
Sensor Native resolution	8.5 MegaPixels
Video resolution/ frame rate	4K UHD @ 30 fps (up to 3840 x 2160 pixels)
Digital Zoom, Pan, Tilt & Zoom (PTZ)	5x Digital Zoom in Full HD Digital PTZ via remote control
Video Codec	MJPEG, YUY2
Image correction	Backlight Compensation (via Remote control), Low-light compensation
Active conference notification	Ring LED
Face/ Human figure detection	No

### Voice

Microphones	6 microphones array
Microphone coverage	180-degrees
Microphone pickup range	Up to 6 m
Beamforming	Yes
Full Duplex	Yes
Frequency response	120 Hz – 16 kHz
Sensitivity	-26 dB +/- 1dB
Sampling rate	48 KHz
Distortion	N/A
Noise Reduction/ Cancelling	Yes - Noise suppressing algorithm
Acoustic Echo Cancelling	Yes
Recommend number of participants	Up to 8
Other Microphone features	AGC (Automatic Gain Control)

### Sound

Speakers	2x 4 cm
Speaker power - Sound Pressure Level (SPL)	85 dB +/- 3 dB
Frequency response	200 Hz – 16 kHz
Sensitivity - Sound Pressure Level (SPL)	85 dB +/- 3dB
Distortion	< 3% @ 200-300 Hz, < 1% 2000 Hz-10 kHz < 1%

### Connectivity

USB	Plug and Play
USB Cable	Included - 2 m USB 3.0 cable
Bluetooth®	No

### General

Remote Control	Included
Remote Control Function	BLC, power, digital pan, tilt, zoom, call answer/end, volume, mute
Remote Control Range	6 m
Power Supply	AC Adapter
Rechargeable battery	No
Wall mount	Included
Monitor mount	Built in - clip-on style
Security slot	No
Warranty	2 years
System Requirements	Windows® 7, Windows 8.1, or Windows 10 macOS 10.10 or higher

### Conference software compatibility

Skype™ for Business	Compatible
Teams®	Compatible
Zoom™	Compatible
Tencent	Compatible
Google™ Hangout	Pending – contact us for latest information
Cisco Jabber® and WebEx	Compatible
BlueJeans	Pending – contact us for latest information
BroadSoft	Pending – contact us for latest information
Vidyo™	Pending – contact us for latest information
UVC USB Video Class	Supported
UAC USB Audio Class	Supported

### Dimensions

Length x Width x Height (cm)	35.2 x 11.85 x 7.55 cm
Weight (kg)	0.89 Kg (AEM350 only) 1.3 Kg (with other accessory)

### Configurations

AEM350UKZ	with UK power adapter only
AEM350EUZ	with EU power adapter only